

Due to the varying characteristics of the material it is impossible to make identical springs. Material hardness, dimension and physical properties can vary, which influences the consistency of the spring.

Tolerance table for coil springs

Diameter D _m (mm)	Tolerance (mm)
0,1 < D _m ≤ 2,5	± 0,12
2,5 < D _m ≤ 4	± 0,15
4 < D _m ≤ 6,3	± 0,2
6,3 < D _m ≤ 10	± 0,25
10 < D _m ≤ 16	± 0,3
16 < D _m ≤ 25	± 0,4
25 < D _m ≤ 40	± 0,5
40 < D _m ≤ 50	± 0,6
50 < D _m ≤ 63	± 0,8
63 < D _m ≤ 80	± 1
80 < D _m ≤ 100	± 1,2
100 < D _m ≤ 125	± 1,5
125 < D _m ≤ 160	± 2

For the end coil of the compression springs, the values of the table A and B should be doubled.

$$D_m = D_y - D_t = D_i + D_t$$

Tolerances for free length (L₀)

Ratio D _m / D _t	Tolerance
4 - 12	±5%
(12) - 15	±7,5%

Lowest tolerance for L₀ = ±0.3 mm

Tolerances for spring force (F)

Ratio D _m / D _t	No of active coils				
	2-3.5	>3.5-5.5	>5.5-8.5	>8.5-12.5	>12.5+
4 - 5	±15%	±12%	±11%	±10%	±9%
(5) - 11	±13%	±11%	±10%	±9%	±8%

Tolerances for Die springs (page 50-67)

LENGTH	Tolerance
Unloaded length, mm	
L0 25-89	+/- 1mm
L0 102-305	+/- 1%

FORCE	Tolerance
Springforce	
General	+/- 10%

Tolerances for other wire and strip steel formations

Base dimension (mm)	Tolerance (mm) Linear dimensions
≤ 3	± 0,2
>3-6	± 0,3
>6-30	± 0,5
>30-120	± 0,8
>120-400	± 1,2
>400-1000	± 2,0

Base dimension (mm)	Tolerance (mm) Bending radius
≤ 3	± 0,2
> 3 - 6	± 0,3
> 6 - 30	± 1,0
> 30 - 60	± 2,0
> 60 - 120	± 4,0
> 120 - 300	± 10,0

Base dimension (mm)	Tolerance (°) Bending angles
≤ 10	± 3
> 10 - 50	± 2
> 50	± 1

Base dimension = shortest leg length

Tolerance for angle deviation

The deviation (A) of the generating line from the vertical line must not be greater than 0.05 L₀ (2.9°). Parallel misalignment (A₁) must not be greater than 0.03 D_y (1.7°).

